

Modello/Model	Senza motore/Without motor ¹	Classe energetica/Energy class ²
FIM 682-90x30	K6068209030EX	C
FIM 682-120x30	K6068212030EX	C
FIM 682-90x50	K6068209050EX	C
FIM 682-120x50	K6068212050EX	C
FIM 682-120x70	K6068212070EX	C
FIM 682-90x30 L	K6068209030EXL	B
FIM 682-120x30 L	K6068212030EXL	B
FIM 682-90x50 L	K6068209050EXL	B
FIM 682-120x50 L	K6068212050EXL	B
FIM 682-120x70 L	K6068212070EXL	B
Finitura/Finish	Acciaio inox satinato Acciaio inox verniciato (colorazioni personalizzate su richiesta)	Stainless steel satin Stainless steel painted (custom colors on request)
Comandi/Controls	Elettronici 3 velocità+intensiva+radiocomando	Electronic 3 speeds+intensive+remote control
Note tecniche/Technical notes		
Portata (m ³ /h)/Airflow (m ³ /h)	638	
Pressione (Pa)/Pressure (Pa)	633	
Rumorosità (Lw[dBA])/Noise level (Lw[dBA])	61	
Potenza motore (W)/Motor power (W)	275	
Illuminazione/Lighting	Lampade alogene 2x20W 12V (90x30/50) 3x20W 12V (120x30/50/70)	Halogen lamps
	Lampade led 3x1,2W 350mA (90x30 L) 4x1,2W 350mA (120x30 L) 6x1,2W 350mA (90x50 L) 8x1,2W 350mA (120x50/70 L)	Led lamps
Versione/Version	Aspirante	Suction
Uscita (mm)/Duct size (mm)	Ø 150+220x90	

¹ Modelli predisposti per i motori remoti (vedi Motori remoti)/Models designed for remote motors (see Remote motors)

² I dati energetici sono stati calcolati con il motore remoto FIM 639/The energy data were calculated with the remote motor FIM 639



